

Datasheet

FUJITSU Image Scanner fi-7260



The fi Series standard combo flatbed / ADF scanner offers superior performance



The fi-7260 scans A4 portraits at 60 ppm/120 ipm (200/300 dpi), loads up to 100 sheets at a time, and ensures utmost efficiency with amazing scanning performance.

Assistance for safe and reliable scanning

The fi-7260 possesses diverse stable paper feeding mechanisms, ensuring speedy and high quality scanning without relying on PC performance. Minimize risk of document damage with Paper Protection function detecting anomalies in sound and monitoring paper feed distance. And bid farewell to missing edges with the scanner's Skew Reducer mechanism. Potential information loss, resulting from multiple sheets being fed through the scanner at once, is also no longer an issue with Ultrasonic Multi-feed detection.

Boosted usability with a user-friendly and versatile design

Equipped with a built-in flatbed, this scanner can scan fragile documents and thick books, impossible to scan with ADF. Start scanning with a single push of a button. Keep track of scanner operations such as document scanning settings, number of sheets scanned, as well as any existing error statuses, using the LCD operation panels. Daily maintenance tasks, including interior cleaning and roller replacement, can also be done with ease for long-lasting utilization.

High quality images in any condition

Enjoy sharp, high quality images with the fi-7260's CCD image sensors. Subtle changes in scanning environment, such as in air temperature and LED illumination, are also no longer a need for concern with the scanner automatically changing background colors to maintain consistently crisp images.

Advanced software for enhanced efficiency

The PaperStream IP scanner driver, supporting both TWAIN and ISIS, enables you to bypass the inconvenience of making fine image processing adjustments each time you scan. The driver automatically cleans scanned images, facilitating OCR accuracy even when scanning documents with background patterns or wrinkled and soiled documents. Seamlessly linked to PaperStream IP, PaperStream Capture offers various batch scanning capture features to effectively and efficiently feed information into your organization workflow. Automatically utilizing data extracted from barcodes and patch codes, the software determines your preferred saving destinations and eliminates time allocated to routine tasks.

Technical Information

Scanner Type		ADF (Automatic Document Feeder) / Flatbed, Duplex
Scanning Speed*1 (A4 Portrait) (Color*2/Grayscale*2/Monochrome*3)		ADF Simplex: 60 ppm (200/300 dpi) Duplex: 120 ipm (200/300 dpi) Flatbed 1.7 seconds (200 dpi)
Image Sensor Type		Color CCD x 3 (front x 1, back x 1, Flatbed x 1)
Light Source		White LED Array x 3
Optical Resolution		(front x 1, back x 1, Flatbed x 1)
Output Resolution*4 (Color / Grayscale / Monochrome)		600 dpi 50 to 600 dpi (adjustable by 1 dpi increments),
Bit Depth		1,200 dpi (driver)*5
Background Colors		48 Bit (Internal), 24 Bit (External)
Document Size		ADF: White / Black (selectable)
ADF	Maximum*6	Flatbed: White (optional black) 216 x 355.8 mm (8.5 x 14 in.)
	Minimum*7	50.8 x 54 mm (2 x 2.1 in.)
	Long Page Scanning*8	5,588 mm (220 in.)
Flatbed	Maximum	216 x 297 mm (8.5 x 11.7 in.)
Paper Weight (Thickness)*9		
Paper		27 to 413 g/m ² (7.2 to 110 lb) *10
Plastic Card		1.4 mm (0.055 in.) or less (ADF) *11
ADF Capacity*12*13		100 sheets (A4 64 g/m ²)
Typical Daily Duty Cycle*14		9,000 sheets
Multifeed Detection		Overlap detection (Ultrasonic sensor), Length detection
Paper Protection		Lag detection, Sound detection (iSOP) *15
Interface*16		USB 3.0 / USB 2.0 / USB 1.1
Power Requirements		AC 100 to 240 V ±10 %
Power Consumption		
Operating Mode		41 W or less
Sleep Mode		1.8 W or less
Auto Standby (Off) Mode		0.35 W or less

In order to avail extended warranty or AMC, please write to fipl-imaging@ts.fujitsu.com.

*1 Actual scanning speeds are affected by data transmission and software processing times. *2 Indicated speeds are from using JPEG compression. *3 Indicated speeds are from using TIFF CCITT Group 4 compression. *4 Selectable maximum density may vary depending on the length of the scanned document. *5 Some limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). *6 Scans folded documents of up to 297 x 432 mm (11.7 x 17 in.) with carrier sheet scanning. *7 Scanning area limitations only apply when using the ADF. There are no limitations when using the flatbed. *8 Capable of scanning documents longer than A4 (210 x 297 mm / 8.3 x 11.7 in.) sizes. When using PaperStream IP (TWAIN/ISIS) to scan at 200 dpi, the maximum scanning length is 5,588 mm (220 in.). *9 Paper weight limitations only apply when using the ADF. There are no limitations when using the flatbed. *10 Thicknesses of up to 127 to 209 g/m² (34 to 56 lb) can be scanned for A8 (52 x 74 mm / 2.1 x 2.9 in.) sizes. *11 Capable of scanning up to 3 cards at a time (Note: does not set more than one embossed card at a time). *12 Maximum capacity depends on paper weight and may vary. *13 Capable of setting additional documents while scanning. *14 This duty cycle is applicable in India and will be supported by Fujitsu India *15 Intelligent Sonic Paper Protection. *16 Connection with USB 3.0 / 2.0 requires the USB port and hub to be connected to the PC. *17 Excludes the ADF paper chute and stacker. *18 Availability of support may vary depending on region. Some functions may not be available with the Image Scanner Driver for Linux. *19 Functions equivalent to those offered by PaperStream IP may not be available with the WIA Driver. *20 Software can be downloaded from the website designated in the Setup DVD-ROM.

Trademarks
ABBYY™ FineReader™ Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies.

Safety Precautions
Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings.

ENERGY STAR®
PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States. Specifications are subject to change without notice.

Contact
ScannerWorld (A div. of Alchemist Softwares Pvt Ltd)
For Sales: sales@alchemistsoftwares.com
For Support: support@alchemistsoftwares.com
Phone: +91 (20) 4130 2020, +91 84080 00266, +91 99230 54123
<https://scannerworld.in>

Operating Environment	
Temperature	5 to 35 °C (41 to 95 °F)
Relative Humidity	20 to 80% (non-condensing)
Environmental Compliance	
ENERGY STAR®, RoHS	
Dimensions*17	
300 x 577 x 234 mm (11.8 x 22.7 x 9.2 in.)	
(Width x Depth x Height)	
8.8 kg (19.4 lb)	
Weight	Windows® 10 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Server® 2016 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit), Linux Ubuntu *18
Supported Operating System	
Included Software / Drivers	
PaperStream IP Driver (TWAIN/TWAIN x64/ISIS), WIA Driver*19, PaperStream Capture, ScanSnap Manager for fi Series*20, Software Operation Panel, Error Recovery Guide, ABBYY FineReader for ScanSnap™*20, Scanner Central Admin	
Image Processing Functions	
Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis, Dropout color (None/Red/Green/Blue/White/Saturation/Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Static threshold, Moire removal	
ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM	
Included Items	

Options

Black Document Pad (FI-728BK)	PA03670-D801Black flatbed background pad
Carrier Sheets	PA03360-0013Each package contains 5 carrier sheets

Consumables

Brake Roller	PA03670-0001	Every 200,000 sheets or one year
Pick Roller	PA03670-0002	Every 200,000 sheets or one year